

# Industrial Display Monitor

## 19" Color TFT Industrial Display Monitor

**ADP-1190**



### Features

- 19" TFT SXGA LCD
- 1280(H)x1024(V), 300 cd/m<sup>2</sup>
- Front Panel NEMA 4/IP 65 rating
- Wall-mount screw holes
- Resistive touch screen (optional)
- Optional DVI, Video or S-Video input
- Optional stainless steel front bezel
- Support wide-ranging resolutions from 640x480 to up to 1600 x 1200 with auto phase and auto position

### Display Specifications

Display	19" Color Active TFT Flat Panel Display
Luminance	300 cd/m <sup>2</sup>
Viewing Angle	160/160 (H/V)
Resolutions	1280 x 1024 ( native mode), 16.7M colors
Backlight Lifetime	50,000hrs
Touch Screen	Analog resistive (optional)
OSD Control	On the back side
I/O Connectors	1xAC power input, 1xVGA, optional:DVI,S-Video,RCA, touch (RS-232 or USB)
Power Input	AC 100~240V, optional DC 11~28V

### Mechanical Specifications

Construction	Steel chassis & front bezel
Dimensions	484(W)x400(H)x71.7(D)mm
Mounting	Panel Mount / Rack Mount (optional)
Weight	8.53kgs

### Environment Specifications

Operating Temperature	0~50°C (32~122°F)
Storage Temperature	-20~60°C (-4~140°F)
Relative Humidity	10~90% @40°C Non-condensing, without touch screen
Vibration	1G peak, 5~500 Hz (Random)
Shock	15G peak acceleration (11 msec. duration)
Rating	NEMA 4/IP 65 compliant front bezel
Certificate	Meet CE / FCC Class A

### Dimensions

